

**New
product**

320A Meter mounting device with bypass mechanism: OH/UG

320A, 600 Volt, single phase service

- CSA approved & complies to CSA C22.2 No 115-20
- Self contained meter socket with bypass mechanism
- Combination unit : Overhead/Underground
- Weather proof 3R enclosure with ANSI 61 grey color
- All Safety Interlocks as per CSA and instruction labels on unit
- Supplied with CSA approved 320A jumper bars
- Lexan shield for additional barriers and helps to guide in the meter
- Insulated safety sheet immediately after removal of cover
- Barriers & meter guide for easy installation
- Heavy duty stainless steel body sealing ring
- Bypass mechanism is accessible to authorized persons only with main covers closed and with standard 3/8" hex key
- Grounded neutral as default feature can be easily converted insulated neutral by just removing bonding strap at site
- Dimension: Inches (HXWXD) 38-7/16X18-5/8X6-13/16
- Trade size knockout: 2,2-1/2,3,3-1/2,4 in: 3 places
- Below list of catalogue number with line and load connections:
- List of OH/UG catalogue number with line and load tunnel type connectors

Meter sockets
Poleline hardware
Electrical enclosure



S. No	Catalogue Number	Application	Line lugs	Load lugs
1	EK320RO	Overhead/ Underground	4-600 MCM or TWO 250MCM-1 /0	4-600MCM or TWO 250MCM-1 /0
2	EK320RO1		TWO 350MCM-6	TWO 350MCM-6
3	EK320RO2		4-600 MCM or TWO 250MCM-1/0	TWO 350MCM-6

Note : For only underground with 1/2" studs please contact Hydrel

Toll free: 1- 800-263-4579

● **hydrelinc.com**

Hydel

206 Great Gulf Drive, Vaughan, Ontario L4K 5W1, Canada
T: 905-669-5511 | Email: sales@hydrelinc.com

Hydel
Sicame Group